

1-Line Ultra Low Capacitance Bi-directional TVS Diode


Description

The PESDR0521P1L is a bi-directional TVS diode, to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high speed data lines. The PESDR0521P1L has an ultra-low capacitance with a typical value at 0.25pF, and complies with the IEC61000-4-2 (ESD) standard with ±20kV air and ±20kV contact discharge. It is assembled into an ultra-small 1.0x0.6x 0.5mm lead-free DFN package. The small size, ultra-low capacitance and high surge protection make PESDR0521P1L an ideal choice to protect cellphone, digital video interfaces and other high speed ports.


Features

- Ultra small package: 1.0x0.6x0.5mm
- Ultra low capacitance: 0.25pF typical
- Low operating voltage: 5 V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: ±20kV
 - Contact discharge: ±20kV
 - IEC61000-4-5 (Lightning) 4A (8/20µs)
- RoHS Compliant

Dimensions and Pin Configuration



Package Dimensions



Circuit and Pin Schematic


Mechanical Characteristics

- Package: DFN1006-2 (1.0x0.6x0.5mm)
- Case Material: “Green” Molding Compound.
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below

Applications

- Cellular Handsets and Accessories
- Display Ports
- MDDI Ports
- USB Ports
- Digital Video Interface (DVI)
- PCI Express and Serial SATA Ports

Marking Information



S/21 = Device Marking Code

Ordering Information

Part Number	Shipping	Reel Size
PESDR0521P1L	10000/Tape & Reel	7 inch

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{PK}	100	W
Peak Pulse Current (8/20 μs)	I_{PP}	5	A
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 20	kV
ESD per IEC 61000-4-2 (Contact)		± 20	
Lead temperature	T_L	260	$^{\circ}\text{C}$
Operating Temperature Range	T_{OP}	-40 ~ +85	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			5	V	
Breakdown Voltage	V_{BR}	5.3		10	V	$I_T = 1\text{mA}$
Reverse Leakage Current	I_R			0.5	μA	$V_{RWM} = 5\text{V}$
Clamping voltage ¹⁾	V_{CL}		35		V	$I_{PP}=16\text{A}$, $t_p=100\text{ns}$
Dynamic resistance ¹⁾	R_{DYN}		0.3		Ω	
Clamping Voltage ²⁾	V_C		35		V	$V_{ESD} = 8\text{kV}$
Clamping Voltage ³⁾	V_C			10.5	V	$I_{PP} = 1\text{A}$ (8/20 μs pulse)
Clamping Voltage ³⁾	V_C			17	V	$I_{PP} = 4\text{A}$ (8/20 μs pulse)
Clamping Voltage ³⁾	V_C			20	V	$I_{PP} = 5\text{A}$ (8/20 μs pulse)
Junction Capacitance	C_J		0.25	0.45	pF	$V_R = 0\text{V}$, $f = 1\text{MHz}$


Notes:

1) TLP parameter: $Z_0 = 50\Omega$, $t_p = 100\text{ns}$, $t_r = 2\text{ns}$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

2) Contact discharge mode, according to IEC61000-4-2.


3) Non-repetitive current pulse, according to IEC61000-4-5.

Electrical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)




Definitions of electrical characteristics


Typical Performance Characteristics (TA=25°C unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power Derating Curve




8/20μs Pulse Waveform




TLP Measurement

DFN1006-2 Package Outline Drawing



Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.340	0.450	0.550
A1	0.000	0.020	0.050
A3	0.125 Ref.		
D	0.950	1.000	1.075
E	0.490	0.600	0.675
b	0.200	0.250	0.300
L	0.450	0.500	0.550
e	0.650 BSC		

Recommended PCB Layout (Unit: mm)




Notes:



This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

TAPE AND REEL INFORMATION


Reel Dimensions



Tape Dimensions



or



User Direction of Feed

IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The **PN SILICON** logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.