

1-Line Bi-directional TVS Diode


Description

The PESDR0361D3 is a 3.3V bi-direction TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high-speed data lines. The PESDR0361D3 has a low capacitance with a typical value at 0.6pF, and complies with the IEC 61000-4-2(ESD) standard with ±30kV air and ±30kV contact discharge. It is assembled into a lead-free SOD-323 package. The small size, low capacitance and high ESD surge protection make PESDR0361D3 an ideal choice to protect cellphone, wireless systems, and communication equipment.

Features

- 400W peak pulse power (8/20µs)
- Ultra low capacitance: 0.6pF typical
- Ultra low leakage: nA level
- Low operating voltage: 3.3 V
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: ±30kV
 - Contact discharge: ±30kV
 - IEC 61000-4-5 (Lightning) 20A (8/20µs)
- RoHS Compliant

Dimensions and Pin Configuration



Circuit and Pin Schematic


Mechanical Characteristics

- Package: SOD-323
- Case Material: “Green” Molding Compound.
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below

Applications

- High-speed data lines
- Smart phones
- USB Ports
- Wireless Systems
- Ethernet10/100/1000 Base T

Marking Information



CC = Device Marking Code

Ordering Information

Part Number	Shipping	Reel Size
PESDR0361D3	3000/Tape &Reel	7 inch


Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{PK}	400	W
Peak Pulse Current (8/20 μs)	I_{PP}	20	A
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	kV
Lead temperature	T_L	260	$^\circ\text{C}$
Operating Temperature Range	T_{OP}	-40 ~ +85	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			3.3	V	
Reverse Breakdown Voltage	V_{BR}	4	5	6	V	$I_T = 1\text{mA}$
Reverse Leakage Current	I_R			200	nA	$V_{RWM} = 3.3\text{V}$
Clamping Voltage	V_C		7	9	V	$I_{PP} = 1\text{A}$ (8/20 μs pulse)
Clamping Voltage	V_C		16	20	V	$I_{PP} = 20\text{A}$ (8/20 μs pulse)
Junction Capacitance	C_J		0.6	0.9	pF	$V_R = 0\text{V}$, $f = 1\text{MHz}$

Electrical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)




Definitions of electrical characteristics


Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time



Clamping Voltage vs. Peak Pulse Current




Power Derating Curve




8/20μs Pulse Waveform

SOD-323 Package Outline Drawing



SYM	DIMENSIONS				
	MILLIMETERS			INCHES	
	MIN	NOM	MAX	MIN	MAX
A	1.50	1.65	1.80	0.060	0.071
B	1.20	1.30	1.40	0.045	0.054
C	2.30	2.50	2.70	0.090	0.107
D	-	-	1.10	-	0.043
E	0.30	-	0.40	0.012	0.016
F	0.10	-	0.25	0.004	0.010
L	0.20	-	0.40	0.008	0.016
H	-	-	0.10	-	0.004


Suggested Land Pattern





SYM	DIMENSIONS	
	MILLIMETERS	INCHES
A	3.15	0.120
B	0.80	0.031
C	0.80	0.031

TAPE AND REEL INFORMATION

Reel Dimensions



Tape Dimensions



User Direction of Feed

IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The **PN SILICON** logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.